

Portable Amplifier Model No. APT-010180

APT Series is an ultra wide band amplifier delivering 100mW of RF power over 1-18GHz. It is designed for convenient and versatile use in test setups and measurement systems where hand portability and ruggedness are important requirements

- 1—18 GHz
- 35dB Gain
- 100mW of RF Power
- Portable
- Outdoor use



General Specifications			
Frequency Range	1-18GHz		
Gain	35dB min.		
Output Power 1dB GCP	20dBm min.		
PSat	21dBm		
Flatness	±2dB		
VSWR Input/Output	2.0:1 max		
Operating Temperature	-10 to +60C		
DC Supply	+12V		
Current	525mA typ.		
RF Connector	SMA Female Input Type N Female Output		
Robust Housing	129 x 84 x 67 mm		
IP Rating	IP66/67		
On/Off Locking Toggle Switch			
XLR DC Socket			
Green LED On/Off Indicator			

Frequency (GHz)	Gain (dB)	P-1dB (dBm)	Input VSWR	Output VSWR
1.0	42.90	23.80	1.39	1.30
10.0	40.50	24.90	1.20	1.51
18.0	40.50	21.00	1.21	1.70

Note 1: The specification is subject to regular reviews and will be updated from time to time as part of our continuing product development and improved spec accuracy.

Note 2: Operation beyond the quoted limits stated above may cause instantaneous and permanent damage.





























