

Atlantic Microwave's Torque Wrenches

- Easy to use
- Cost Effective
- Stock Availability

Torque wrenches enable the correct installation or disassembly of a wide range of coaxial connectors. Designed with a pre-set torque value, which when reached will "break" about the pivot pin. Supplied in a wooden box as standard.



GENERAL SPECIFICATIONS

Part No.	For Use with Connector Type	Wrench Size		Pre-set Torque	
		mm	inches	In. lbs	Nm
ATW-S01	SMA/3.5mm/2.92mm/2.4mm/1.85mm	8.0	5/16	8.1 +/- 0.4	0.92 +/- 0.05
ATW-K02	3.5mm/2.92mm/2.4mm/1.85mm	8.0	5/16	12.0 +/- 0.7	1.36 +/- 0.08
ATW-N03	Type N	19.1	3/4	8.1 +/- 0.4	0.92 +/- 0.05
ATW-N04	Type N/7mm (Stainless Steel)	19.1	3/4	14.0 +/- 0.8	1.60 +/- 0.09
ATW-N05	Type N	20.0	25/32	8.1 +/- 0.4	0.92 +/- 0.05
ATW-N06	Type N (Stainless Steel)	20.0	25/32	14.0 +/- 0.8	1.60 +/- 0.09
ATW-SC07	SC/Type N	20.6	13/16	8.1 +/- 0.4	0.92 +/- 0.05
ATW-SC08	SC/Type N (Stainless Steel)	20.6	13/16	14.0 +/- 0.8	1.60 +/- 0.09
ATW-TNC09	TNC (Stainless Steel)	14.3	9/16	12.0 +/- 0.7	1.36 +/- 0.09
ATW-TNC10	TNC (Stainless Steel)	15.9	5/8	12.0 +/- 0.7	1.36 +/- 0.09
ATW-SMC11	SMC	6.0	15/64	3.0 +/- 0.15	0.36 +/- 0.02
ATW-SMC12	SSMC	4.0	5/32	2.0 +/- 0.1	0.23 +/- 0.01
ATW-SS13	SSMA	6.4	1/4	5.0 +/- 0.2	0.57 +/- 0.02
ATW-SS14	SSMA (Stainless Steel)	6.4	1/4	8.1 +/- 0.4	0.92 +/- 0.05
ATW-SH15	SMA Hermetic	7.1	9/32	30.0 +/- 2.0	3.40 +/- 0.23
ATW-1MM	1mm	6.0	15/64	4.0 +/- 0.15	0.45 +/- 0.02
ATW-716	7/16	32.0	1 1/4	20.0 +/- 1.5	2.26 +/- 0.17
ATW-717	7/16	27.0	1 1/16	20.0 +/- 1.5	2.26 +/- 0.17
ATW-TNC18	TNC	14.3	9/16	6.1 +/- 0.3	0.69 +/- 0.03
ATW-TNC19	TNC	15.9	5/8	6.1 +/- 0.3	0.69 +/- 0.03
ATW-S20	SMA (recommended for test application)	8.0	5/16	5.0 +/- 0.2	0.56 +/- 0.02

